


AGRIMAX RT 855

TIRE SIZE	480/80 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	158 A8/B



DIMENSIONER IS STANDARD

SW (MM)	479	RIM REC	DW 16 A; W 16 A; DD 16
OD (MM)	1936	RIM ALT	W 16 L; DD 16 L; DW 16 L
SLR (MM)	895	ECE	E4-106R-001731
RC (MM)	5871	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	2000	2295	2635	2975	3315	3655	3955	4250
40	2000	2295	2635	2975	3315	3655	3955	4250
30	2140	2460	2825	3185	3550	3915	4235	4550
10 LT	2680	3080	3535	3990	4445	4900	5300	5695
10 HT	2140	2460	2825	3185	3550	3915	4235	4550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.