

AGRIMAX RT 765

TIRE SIZE	260/70 R 20
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	113 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94044221	RC (IN)	103.9
SW (IN)	10.2	RIM REC	W 8
OD (IN)	34.3	RIM ALT	9 ; W 9
SLR (IN)	15.8	ECE	E4-106R-000640

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1200	1380	1580	1770	1980	2180	2360	2540
25	1200	1380	1580	1770	1980	2180	2360	2540
20	1290	1480	1700	1910	2130	2350	2540	2720
5 LT	1610	1840	2120	2390	2670	2930	3170	3410
5 HT	1290	1480	1700	1910	2130	2350	2540	2720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.