

AGRIMAX RT 855

TIRE SIZE	320/85 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	SPECIAL
TL/TT	TL
LI/SS	143 A8/B



DIMENSIONS IS STANDARD

SW (MM)	329	RIM REC	W 11
OD (MM)	1509	RIM ALT	W 9 ; W 10 ; DW 10
SLR (MM)	700	ECE	E4-106R-000781
RC (MM)	4580	SRI	725

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	985	1145	1500	1830	1990	2130	2320	2510	2725
40	985	1145	1500	1830	1990	2130	2320	2510	2725
30	1055	1230	1610	1960	2135	2280	2485	2690	2920
10 LT	1320	1540	2015	2450	2670	2855	3110	3365	3655
10 HT	1055	1230	1610	1960	2135	2280	2485	2690	2920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.