

# MULTIMAX MP 522

<b>TIRE SIZE</b>	<b>440/80 R 24 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CARGADORA COMPACTA / ELEVADOR TELESCÓPICO / CARGADORA COMPACTA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	161 A8/B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94052257	<b>RC (IN)</b>	155.8
<b>SW (IN)</b>	17.4	<b>RIM REC</b>	DW 14 L
<b>OD (IN)</b>	51.7	<b>RIM ALT</b>	DW 13 ; DW 13 L ; DW 15 L
<b>SLR (IN)</b>	23.1	<b>ECE</b>	E11-106R-002966

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
<b>30</b>	4890	5820	6640	7550	8470	9080	10200	-	-
<b>25</b>	4890	5820	6640	7550	8470	9080	10200	-	-
<b>20</b>	5250	6230	7100	8080	9060	9720	10910	-	-
<b>15</b>	5430	6460	7360	8380	9400	10090	11320	-	-
<b>5 CYC.</b>	5970	7350	8650	9950	11330	12320	13930	14690	15300
<b>STATIC</b>	9150	11260	13260	15260	17360	18890	21350	22520	23460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.