

# FLOTATION 648

<b>TIRE SIZE</b>	<b>550/60 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	☒ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	DUAL BEAD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	158 A8/154 B
<b>LI/SS FREE ROLLING</b>	171 A8/167 B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	550	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1240	<b>ECE</b>	E11-106R-004391
<b>SLR (MM)</b>	540	<b>PR</b>	20
<b>RC (MM)</b>	3725		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.30	3.40	3.50
10 FR	8315	8465	8610
20 FR	7485	7615	7750
30 FR	6655	6770	6890
40 FR	5940	6045	6150
50 FR	5345	5440	5450
10 DW	5745	5850	5950
20 DW	5170	5265	5355
30 DW	4600	4680	4760
40 DW	4105	4180	4250
50 DW	3625	3685	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.