


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>380/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	125 D



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94062607	<b>RC (IN)</b>	140.2
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	46.9	<b>RIM ALT</b>	W 11; W 13
<b>SLR (IN)</b>	21.2	<b>ECE</b>	E11-106R-005767

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	2010	2340	2660	2990	3320	3640
30	2110	2460	2800	3140	3480	3820
25	2200	2560	2920	3270	3640	3990
20	2300	2690	3060	3440	3810	4190
5 LT	2690	3130	3570	4010	4450	4880
5 HT	2300	2690	3060	3440	3810	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.