

# AGRIMAX V- FLECTO

**VF 650/70 R 34 NRO**

<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	170 D



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	603	<b>RIM REC</b>	DW 21 B
<b>OD (MM)</b>	1704	<b>RIM ALT</b>	DW 20 B
<b>SLR (MM)</b>	740	<b>ECE</b>	E11-106R-008813
<b>RC (MM)</b>	5025	<b>SRI</b>	800

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2730	3165	3600	4095	4530	4965	5460
<b>FROM 65 TO 40</b>	3000	3480	3960	4500	4980	5460	6000
30	3060	3545	4035	4590	5075	5565	6120
20	3120	3615	4115	4680	5175	5675	6240
10	3300	3825	4355	4950	5475	6005	6600
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	4200	4870	5540	6300	6970	7640	8400
10 HT	3060	3545	4035	4590	5075	5565	6120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.