


AGRIMAX V- FLECTO



| | |
|---------------------|--|
| TIRE SIZE | VF 600/60 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HIGH-POWER TRACTOR / TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 157 D |

DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94058495 | RC (IN) | 166.5 |
| SW (IN) | 23.1 | RIM REC | DW 20 B |
| OD (IN) | 56.7 | RIM ALT | DW 18 L |
| SLR (IN) | 24.9 | ECE | E11-106R-004471 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|--------------------------------------|------|------|------|-------|-------|-------|
| 45 | 4540 | 5290 | 6030 | 6780 | 7520 | 8270 |
| FROM 40 TO 25 | 4990 | 5820 | 6640 | 7450 | 8270 | 9095 |
| 20 | 5090 | 5930 | 6770 | 7590 | 8430 | 9270 |
| 12 | 5190 | 6050 | 6900 | 7750 | 8600 | 9460 |
| 5 | 5490 | 6390 | 7300 | 8190 | 9090 | 10000 |
| *UPTO 5 CYC WITH FRONT LOADER | 6990 | 8150 | 9280 | 10430 | 11570 | 12730 |
| 5 HT | 5090 | 5930 | 6770 | 7590 | 8430 | 9270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.