


AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 7.5L - 15 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO |
| VERSIONE | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 100 A8 |
| LI/SS FREE ROLLING | 113 A8 |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CODICE USA | 94019403 | RC (IN) | 89.8 |
| SW (IN) | 8.3 | RIM REC | 6 LB |
| OD (IN) | 30.1 | RIM ALT | 5 K; 5½ J; 5½ K |
| SLR (IN) | 13.9 | ECE | E4-106R-002632 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 54 |
|-----------|------|
| 5 FR | 3550 |
| 15 FR | 3020 |
| 20 FR | 2840 |
| 25 FR | 2540 |
| 5 DW | 2470 |
| 15 DW | 2090 |
| 20 DW | 1970 |
| 25 DW | 1760 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.