DATA SHEET

PRINTED ON
23-04-2026

AW 702

TIRE SIZE	**10.5/65 - 16**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / REMORCĂ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS FREE ROLLING	123 A8

DIMENSIUNI IS STANDARD

SW (MM)	270	**RIM REC**	W 9
OD (MM)	760	**RIM ALT**	W 8; W 8 L
SLR (MM)	350	**ECE**	E11-106R-004245
RC (MM)	2329	**PR**	10

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.80
10 FR	2170
25 FR	1845
30 FR	1735
40 FR	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..