

AW 702

| | |
|---------------------------|---------------------------------------------------------------------------------------------------------|
| TIRE SIZE | 11.5/80 - 15.3 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | PRESSE À PAILLE / OUTILLAGE AGRICOLE / REMORQUE / MOISSONNEUSE / OUTILLAGE AGRICOLE / REMORQUE |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS FREE ROLLING | 135 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| CODE USA | 94009404 | RC (IN) | 97.4 |
| SW (IN) | 11.7 | RIM REC | 9.00 |
| OD (IN) | 33.2 | ECE | E4-106R-001895 |
| SLR (IN) | 14.6 | PR | 12 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 59 |
|-----------|------|
| 5 FR | 6720 |
| 15 FR | 5720 |
| 20 FR | 5380 |
| 25 FR | 4810 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.