


EARTHMAX SR 22 AS

| | |
|--------------|--|
| TIRE SIZE | 23.5 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HJULLASTARE / VÄGHYVLARE |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 185 B ; 170 A8 ; 201 A2 |



DIMENSIONER US STANDARD

| | | | |
|----------|----------|-------------|-----------|
| USA CODE | 94073405 | RIM REC | 19.50/2.5 |
| OD (IN) | 63.5 | TRA CODE | E2/G2/L2 |
| SLR (IN) | 27.9 | STAR RATING | ★★/★/★★ |
| RC (IN) | 191.5 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 18 | 22 | 25 | 29 | 33 | 36 | 40 | 44 | 58 | 62 | 65 | 69 | 73 | 76 | 80 | 83 | 87 | 91 |
|------------------|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | - | - | - | - | - | - | - | - | 16500 | 17100 | 18200 | 18700 | 19800 | 20400 | - | - | - | - |
| 25 | 6950 | 7850 | 8800 | 9900 | 10700 | 11700 | 12300 | 13200 | - | - | - | - | - | - | - | - | - | - |
| 5 | - | - | - | - | - | - | - | - | - | - | - | - | - | 27600 | 28300 | 29100 | 30000 | 30900 |
| MPH / PSI | 94 | | | | | | | | | | | | | | | | | |
| 30 | - | | | | | | | | | | | | | | | | | |
| 25 | - | | | | | | | | | | | | | | | | | |
| 5 | 32000 | | | | | | | | | | | | | | | | | |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.