

# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>320/70 R 20</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | BESPRUTNINGSBIL / TRAKTOR /<br>SKÖRDEMASKIN FÖR VINGÅRD /<br>SKÖRDEMASKIN / ARBETSFORDON |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 123 A8/B   |



## DIMENSIONER IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 319  | <b>RIM REC</b> | W 10           |
| <b>OD (MM)</b>  | 982  | <b>RIM ALT</b> | W 9; W 11      |
| <b>SLR (MM)</b> | 445  | <b>ECE</b>     | E4-106R-000644 |
| <b>RC (MM)</b>  | 2938 | <b>SRI</b>     | 475            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|-----|------|------|------|------|------|------|------|
| 50         | 730 | 840  | 965  | 1085 | 1210 | 1335 | 1445 | 1550 |
| 40         | 730 | 840  | 965  | 1085 | 1210 | 1335 | 1445 | 1550 |
| 30         | 785 | 900  | 1030 | 1165 | 1295 | 1430 | 1545 | 1660 |
| 10 LT      | 980 | 1125 | 1290 | 1460 | 1625 | 1790 | 1935 | 2080 |
| 10 HT      | 785 | 900  | 1030 | 1165 | 1295 | 1430 | 1545 | 1660 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.