

AGRIMAX RT 855

TIRE SIZE	460/85 R 34
UM	US STANDARD
CONSTRUCTION	
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	158 A8/B



DIMENSIONS US STANDARD

USA CODE	94047772	RC (IN)	191.5
SW (IN)	18.7	RIM REC	W 16 L
OD (IN)	64.8	RIM ALT	W 14 L ; W 15 L
SLR (IN)	28.4	ECE	E11-106R-006759

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
30	3660	4310	4970	5530	6180	6750	7410	7970	8720	9370
25	3660	4310	4970	5530	6180	6750	7410	7970	8720	9370
20	3910	4620	5320	5920	6620	7230	7930	8530	9340	10030
5 LT	4910	5780	6660	7420	8290	9050	9920	10680	11680	12550
5 HT	4190	4950	5700	6340	7090	7740	8490	9130	9990	10740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.