


AGRIMAX SPARGO SB

TIRE SIZE	VF 420/85 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR / PULVERIZATOR
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	165 D



DIMENSIONI US STANDARD

USA CODE	94513598	RC (IN)	188.1
SW (IN)	16.9	RIM REC	DW 15 L
OD (IN)	62.1	RIM ALT	DW 14 L
SLR (IN)	28.2	ECE	E11-106R-0010943

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	26	29	32	35	37	41	43	46
45	5580	6200	6940	7580	8000	8300	8610	8930	9350	9780	10090	10510
FROM 40 TO 25	6020	6700	7500	8180	8640	8970	9320	9660	10110	10560	10910	11360
20	6160	6840	7650	8350	8810	9150	9510	9860	10320	10790	11130	11590
12	6280	6970	7800	8510	8990	9340	9690	10050	10520	10990	11360	11820
5	6630	7370	8250	9000	9510	9870	10240	10620	11130	11620	12000	12490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.