


RM 500

| | |
|---------------------|--|
| TIRE SIZE | 500/80 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HARVESTER |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 176 A8 ; 164 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94063697 | RC (IN) | 171.5 |
| SW (IN) | 19.8 | RIM REC | W 16 L |
| OD (IN) | 58.9 | RIM ALT | W 15 L |
| SLR (IN) | 25.0 | ECE | E11-106R-005990 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 |
|------------------------|------|------|------|------|-------|-------|-------|-------|
| 25 FREE ROLLING | 6110 | 7040 | 7830 | 9710 | 11120 | 12840 | 14560 | 15650 |
| 25 DRIVE WHEEL | 4300 | 4960 | 5510 | 6830 | 7830 | 9040 | 10250 | 11020 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.