

# AGRIMAX RT 765

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>240/70 R 16</b>                                                              |
| <b>UM</b>        | US STANDARD                                                                     |
| <b>MACHINERY</b> | PULVERIZADOR / TRACTOR /<br>VENDIMIADORA / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>   | STANDARD                                                                        |
| <b>TIRE TYPE</b> | TL                                                                              |
| <b>LI/SS</b>     | 104 A8/B                                                                        |



## DIMENSIONES US STANDARD

|                   |          |                                      |                |
|-------------------|----------|--------------------------------------|----------------|
| <b>CÓDIGO USA</b> | 94022014 | <b>RIM REC</b>                       | W 8            |
| <b>SW (IN)</b>    | 9.6      | <b>RIM ALT</b>                       | W 8 L ; W 9 L  |
| <b>OD (IN)</b>    | 29.2     | <b>ECE</b>                           | E4-106R-000609 |
| <b>SLR (IN)</b>   | 13.2     | <b>TRA CODE</b>                      | R1W            |
| <b>RC (IN)</b>    | 85.7     | <b>TREAD DEPTH (32<sup>nd</sup>)</b> | 35.91          |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-------------|------|------|------|------|------|------|------|------|
| <b>30</b>   | 940  | 1080 | 1230 | 1390 | 1550 | 1710 | 1850 | 1980 |
| <b>25</b>   | 940  | 1080 | 1230 | 1390 | 1550 | 1710 | 1850 | 1980 |
| <b>20</b>   | 1000 | 1160 | 1320 | 1500 | 1660 | 1830 | 1980 | 2130 |
| <b>5 LT</b> | 1260 | 1440 | 1660 | 1870 | 2080 | 2300 | 2490 | 2670 |
| <b>5 HT</b> | 1000 | 1160 | 1320 | 1500 | 1660 | 1830 | 1980 | 2130 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.