


EARTHMAX SR 55

| | |
|---------------------|--|
| TIRE SIZE | 29.5 R 29 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BULLDOZER / GRUVLASTMASKIN / HJULLASTARE |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 223 A2 |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|-----------|--------------------|----------------------|
| OD (MM) | 2009 | RIM ALT | 24.00/3.5; 26.00/3.5 |
| SLR (MM) | 911 | TRA CODE | L5S |
| RC (MM) | 6047 | STAR RATING | ★★★ |
| RIM REC | 25.00/3.5 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 | 7.25 | 7.50 | 7.75 | 8.00 |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 10 | 19500 | 20000 | 20600 | 21200 | 22400 | 23000 | 23600 | 24300 | 25000 | 25750 | 26500 | 26500 | 27250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.