


# EARTHMAX SR 45 PLUS

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>33.00 R 51</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | RIGID DUMP TRUCK   |
| <b>VERSION</b>      | STANDARD COMPOUND  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 235 B  |



## DIMENSIONS IS STANDARD

|                 |           |                    |    |
|-----------------|-----------|--------------------|----|
| <b>OD (MM)</b>  | 3065      | <b>TRA CODE</b>    | E4 |
| <b>SLR (MM)</b> | 1369      | <b>STAR RATING</b> | ★★ |
| <b>RC (MM)</b>  | 9313      |                    |    |
| <b>RIM REC</b>  | 24.00/5.0 |                    |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00  | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 30000 | 30750 | 32500 | 33500 | 34500 | 35500 | 36500 | 37500 | 38750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.