

# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 380/90 R 46 CFO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94518494	<b>RC (IN)</b>	220.9
<b>SW (IN)</b>	15.4	<b>RIM REC</b>	DW 13 A
<b>OD (IN)</b>	72.9	<b>RIM ALT</b>	W 13 A ; DW 12
<b>SLR (IN)</b>	33.4	<b>ECE</b>	E11-106R-007527-01

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64	67
<b>45</b>	6250	7040	7690	8080	8470	8730	9000	9520	9910	10300	10700	11080	11350	11730	12000	12520	13040	13690
<b>FROM 40 TO 25</b>	6880	7740	8460	8890	9320	9610	9890	10470	10900	11330	11750	12180	12470	12900	13190	13760	14330	15220
<b>20</b>	7020	7900	8620	9070	9500	9790	10080	10660	11100	11550	11990	12430	12710	13150	13440	14030	14620	15520
<b>12</b>	7150	8050	8790	9240	9680	9980	10280	10870	11330	11780	12220	12670	12970	13410	13710	14300	14910	15830
<b>5*</b>	7570	8510	9300	9770	10240	10560	10870	11500	11980	12450	12920	13400	13720	14190	14500	15130	15770	16740
<b>UPTO 10 CYC.</b>	9330	10500	11470	12050	12640	13020	13410	14180	14760	15350	15930	16520	16900	17490	17870	18660	19430	20620
<b>UPTO 20 CYC.</b>	7820	8800	9610	10100	10590	10920	11240	11890	12370	12870	13350	13840	14170	14650	14980	15630	16290	17280

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.