

AGRIMAXFACTOR

TIRE SIZE	710/70 R 42
UM	IS STANDARD
MACHINERY	ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	173 D ; 176 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	716	RIM ALT	DW 25 B
OD (MM)	2061	ECE	E11-106R-007526
SLR (MM)	935	SRI	975
RC (MM)	6198	TRA CODE	R1W
RIM REC	DW 23 B	TREAD DEPTH (MM)	58

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	3055	3510	4030	4550	5070	5590	6110	6500
50	3210	3690	4235	4780	5325	5870	6420	6825
40	3340	3835	4405	4970	5540	6110	6675	7100
30	3515	4040	4635	5235	5835	6430	7030	7475
10 LT	4095	4705	5405	6100	6795	7495	8190	8710
10 HT	3515	4040	4635	5235	5835	6430	7030	7475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.