


# AS 505

<b>TIRE SIZE</b>	<b>6.5/80 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	86 A8
<b>LI/SS FREE ROLLING</b>	98 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94019465	<b>RC (IN)</b>	82.9
<b>SW (IN)</b>	6.7	<b>RIM REC</b>	5.0
<b>OD (IN)</b>	27.4	<b>RIM ALT</b>	4½ K; 5 K; 5 J
<b>SLR (IN)</b>	12.8	<b>ECE</b>	E4-106R-002188

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	52
5 FR	2310
15 FR	1970
20 FR	1850
25 FR	1650
5 DW	1630
15 DW	1390
20 DW	1310
25 DW	1170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.