

# LG 306

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>16X6.50 - 8</b>                       |
| <b>UM</b>           | IS STANDARD                              |
| <b>CONSTRUCTION</b> | ❖ BIAS                                   |
| <b>MACHINERY</b>    | ÅKGRÄSKLIPPARE / LITEN TRAKTOR / TRAKTOR |
| <b>VERSION</b>      | STANDARD                                 |
| <b>TIRE TYPE</b>    | TL                                       |



## DIMENSIONER IS STANDARD

|                 |      |                |                              |
|-----------------|------|----------------|------------------------------|
| <b>SW (MM)</b>  | 170  | <b>RIM REC</b> | 5.375   - 55;   - 70;   - 90 |
| <b>OD (MM)</b>  | 408  | <b>ECE</b>     | E4-106R-002175               |
| <b>SLR (MM)</b> | 182  | <b>PR</b>      | 6                            |
| <b>RC (MM)</b>  | 1183 |                |                              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.90</b> |
| 15                | 355         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.