

AGRIMAX RT 765

TIRE SIZE	420/70 R 28
UM	US STANDARD
MACHINERY	FELDSPRITZE / TRACTOR / TRAUBENERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	133 D



ABMESSUNGEN US STANDARD

USA-CODE	94062263	RIM REC	W 13
SW (IN)	16.5	RIM ALT	W 12 ; W 14 L
OD (IN)	53.1	ECE	E11-106R-005520
SLR (IN)	23.8	TRA CODE	R1W
RC (IN)	158.3	TREAD DEPTH (32nd)	54.81

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	2500	2910	3320	3730	4130	4540
30	2630	3060	3490	3920	4350	4770
25	2740	3200	3640	4090	4540	4980
20	2880	3350	3820	4290	4760	5220
5 LT	3360	3900	4450	5000	5560	6100
5 HT	2880	3350	3820	4290	4760	5220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.