


MULTIMAX MP 515

| | |
|---------------------|--|
| TIRE SIZE | 425/75 R 20 MPT |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VEHICUL UNIVERSAL / CAMION PENTRU ÎNGRĂȘĂMINTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 148 G |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|--------------------------------|
| USA CODE | 94055975 | RC (IN) | 137.4 |
| SW (IN) | 16.6 | RIM REC | 13 |
| OD (IN) | 45.1 | RIM ALT | 13 SDC; 11 SDC; 12 SDC; 11; 12 |
| SLR (IN) | 20.6 | ECE | E11-54R-0017872 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 36 | 44 | 51 | 58 |
|-----------|------|------|------|------|------|------|
| 55 | 3390 | 3990 | 4740 | 5490 | 6220 | 6940 |
| 40 | 3690 | 4330 | 5150 | 5960 | 6750 | 7540 |
| 25 | 3910 | 4600 | 5460 | 6320 | 7150 | 7990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.