


# MULTIMAX MP 522

<b>TIRE SIZE</b>	<b>280/80 R 18 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	KOMPAKTHJULLASTARE / TELESKOPLASTARE / KOMPAKTHJULLASTARE / TELESKOPLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	132 A8/B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94045044	<b>RC (IN)</b>	108.2
<b>SW (IN)</b>	11.1	<b>RIM REC</b>	W 9; 9; 9 SDC
<b>OD (IN)</b>	35.7	<b>RIM ALT</b>	W 8; W 10
<b>SLR (IN)</b>	16.6	<b>ECE</b>	E11-106R-002962

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	2120	2510	2870	3260	3660	3920	4410	-	-
25	2120	2510	2870	3260	3660	3920	4410	-	-
20	2270	2690	3080	3490	3920	4200	4720	-	-
15	2360	2800	3190	3630	4070	4360	4890	-	-
5 CYC.	2580	3170	3740	4300	4890	5320	6020	6350	6610
STATIC	3960	4870	5730	6590	7510	8170	9240	9740	10140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.