


AGRIMAX TURF RT 333

TIRE SIZE	200/70 R 16
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / МАШИНА ДЛЯ СБОРА ФРУКТОВ / МИНИ- ТРАКТОР / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	94 A8/B



РАЗМЕРЫ IS STANDARD

SW (MM)	200	RIM REC	W 6
OD (MM)	686	ECE	E11-106R-008659
SLR (MM)	317	SRI	330
RC (MM)	2054	TRA CODE	R1W

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	315	365	420	470	525	580	625	670
40	315	365	420	470	525	580	625	670
30	340	390	450	505	565	620	670	720
10 LT	425	490	560	630	705	775	840	900
10 HT	340	390	450	505	565	620	670	720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.