

## TR 135

|                  |                     |
|------------------|---------------------|
| <b>TIRE SIZE</b> | <b>13.6 - 24</b>    |
| <b>UM</b>        | IS STANDARD         |
| <b>MACHINERY</b> | TRACTEUR / REMORQUE |
| <b>VERSION</b>   | STANDARD            |
| <b>TIRE TYPE</b> | TT                  |
| <b>LI/SS</b>     | 130 A6              |



### DIMENSIONS IS STANDARD

|                 |      |                         |                |
|-----------------|------|-------------------------|----------------|
| <b>OD (MM)</b>  | 1220 | <b>ECE</b>              | E4-106R-001556 |
| <b>SLR (MM)</b> | 562  | <b>PR</b>               | 12             |
| <b>RC (MM)</b>  | 3698 | <b>TRA CODE</b>         | R1             |
| <b>RIM REC</b>  | W 12 | <b>TREAD DEPTH (MM)</b> | 35,5           |
| <b>RIM ALT</b>  | W 11 |                         |                |

### LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.90</b> |
| 30                | 1900        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.