


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 600/60 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94065356	<b>RC (IN)</b>	199.9
<b>SW (IN)</b>	23.1	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	66.3	<b>RIM ALT</b>	DW 18 L
<b>SLR (IN)</b>	29.8	<b>ECE</b>	E11-106R-006414

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5170	5960	6860	7640	8540	9330	10450	11230
<b>FROM 40 TO 25</b>	5690	6550	7540	8400	9390	10250	11490	12350
20	5800	6680	7680	8560	9570	10450	11720	12590
12	5910	6800	7840	8730	9750	10660	11940	12830
5	6250	7200	8290	9240	10330	11280	12630	13580
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	7960	9170	10550	11760	13140	14350	16080	17280
5 HT	5800	6680	7680	8560	9570	10450	11720	12590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.