


RIDEMAX IT 696

| | |
|---------------------|--|
| TIRE SIZE | 440/80 R 28 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 156 A8 ; 151 D |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94034895 | RC (IN) | 168.8 |
| SW (IN) | 17.4 | RIM REC | W 14 L |
| OD (IN) | 55.7 | RIM ALT | W 15 L |
| SLR (IN) | 25.0 | ECE | E4-106R-002299 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|------|------|------|------|------|
| 40 | 3570 | 4410 | 5170 | 6010 | 6770 | 7610 |
| 30 | 3890 | 4810 | 5630 | 6550 | 7370 | 8290 |
| 25 | 4140 | 5110 | 6000 | 6970 | 7850 | 8820 |
| 20 | 4310 | 5320 | 6240 | 7240 | 8160 | 9170 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.