

AGRIMAX RT 765

TIRE SIZE	710/70 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
VERSIONE	SPECIAL
TIRE TYPE	TL
LI/SS	176 D ; 179 A8



DIMENSIONI IS STANDARD

SW (MM)	716	RIM REC	DW 23 B
OD (MM)	2061	RIM ALT	DW 25 B
SLR (MM)	922	ECE	E11-106R-006001
RC (MM)	6174	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
65	3055	3550	4050	4545	5045	5540	6110	6465	7100
50	3210	3730	4250	4775	5295	5815	6415	6785	7455
40	3335	3875	4420	4960	5505	6045	6665	7055	7750
30	3515	4085	4655	5230	5800	6370	7025	7435	8165
10 LT	4095	4760	5425	6090	6760	7425	8185	8660	9515
10 HT	3515	4085	4655	5230	5800	6370	7025	7435	8165

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.