

AGRIMAX RT 855

TIRE SIZE	380/85 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	137 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94021697	RC (IN)	177.3
SW (IN)	15.0	RIM REC	W 12
OD (IN)	59.4	RIM ALT	W 11; W 13
SLR (IN)	26.9	ECE	E4-106R-000655

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2790	3250	3700	4170	4620	5080
25	2790	3250	3700	4170	4620	5080
20	3000	3480	3970	4460	4950	5430
5 LT	3750	4350	4970	5580	6190	6800
5 HT	3000	3480	3970	4460	4950	5430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.