


AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 6.5/80 - 12 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO |
| VERSÃO | HD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 80 A8 |
| LI/SS FREE ROLLING | 93 A8 |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94043828 | RC (IN) | 72.3 |
| SW (IN) | 6.7 | RIM REC | 5 J |
| OD (IN) | 23.9 | RIM ALT | 5 JA |
| SLR (IN) | 11.1 | ECE | E11-106R-004088 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 52 |
|-----------|------|
| 5 FR | 2010 |
| 15 FR | 1710 |
| 20 FR | 1610 |
| 25 FR | 1430 |
| 5 DW | 1390 |
| 15 DW | 1180 |
| 20 DW | 1110 |
| 25 DW | 990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.