


# RIB 713

<b>TIRE SIZE</b>	<b>IF 280/70 R 15</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	LANDWIRTSCHAFTLICHE GERÄTE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	128 D



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	279	<b>RIM REC</b>	W 8
<b>OD (MM)</b>	779	<b>ECE</b>	E4-106R-001820
<b>SLR (MM)</b>	347	<b>SRI</b>	360
<b>RC (MM)</b>	2356	<b>TRA CODE</b>	I1

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
FROM 10 TO 65 KM/H	670	775	885	1010	1120	1225	1335	1425	1570	1695	1800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.