


AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 210/95 R 32 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IRRORAZIONE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 120 A8/B |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 214 | RIM REC | W 7 |
| OD (MM) | 1213 | RIM ALT | W 6 |
| SLR (MM) | 571 | ECE | E4-106R-001391 |
| RC (MM) | 3703 | SRI | 575 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 |
|------------|-----|------|------|------|------|------|------|------|
| 50 | 645 | 830 | 1010 | 1095 | 1190 | 1305 | 1400 | - |
| 40 | 645 | 830 | 1010 | 1095 | 1190 | 1305 | 1400 | - |
| 30 | 690 | 885 | 1080 | 1170 | 1275 | 1395 | 1500 | - |
| 10 | 905 | 1180 | 1430 | 1555 | 1660 | 1830 | 1975 | 2100 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.