

# LG 408

|                     |                                 |
|---------------------|---------------------------------|
| <b>TIRE SIZE</b>    | 26.5X14.00 - 12                 |
| <b>UM</b>           | US STANDARD                     |
| <b>CONSTRUCTION</b> | ⊠ BIAS                          |
| <b>MACHINERY</b>    | MOWER / SMALL TRACTOR / TRACTOR |
| <b>VERSION</b>      | STANDARD                        |
| <b>TIRE TYPE</b>    | TL                              |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94012893 | <b>RC (IN)</b> | 75.9            |
| <b>SW (IN)</b>  | 15.0     | <b>RIM REC</b> | 12.00 I         |
| <b>OD (IN)</b>  | 26.2     | <b>ECE</b>     | E11-106R-003353 |
| <b>SLR (IN)</b> | 11.5     | <b>PR</b>      | 6               |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>30</b> |
| 10               | 2820      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.