


AGRIMAX V- FLECTO

TIRE SIZE	VF 540/65 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	158 D



DIMENSIONS US STANDARD

USA CODE	94062133	RC (IN)	171.3
SW (IN)	21.6	RIM REC	DW 20 B
OD (IN)	57.6	RIM ALT	DW 18 L
SLR (IN)	25.6	ECE	E11-106R-005711

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	4340	5020	5700	6470	7070	7670	8520
FROM 40 TO 25	4770	5520	6270	7120	7770	8430	9370
20	4860	5630	6390	7250	7930	8600	9560
12	4960	5740	6510	7400	8080	8760	9740
5	5250	6070	6890	7830	8540	9270	10310
*UPTO 5 CYC WITH FRONT LOADER	6680	7730	8770	9960	10880	11810	13120
5 HT	4860	5630	6390	7250	7930	8600	9560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.