


# FARM 2000

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>14.9 - 28</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRAKTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 136 A6   |



## DIMENSIONER IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 385  | <b>RIM REC</b> | W 13            |
| <b>OD (MM)</b>  | 1375 | <b>RIM ALT</b> | W 11; W 12      |
| <b>SLR (MM)</b> | 636  | <b>ECE</b>     | E11-106R-005968 |
| <b>RC (MM)</b>  | 4194 | <b>PR</b>      | 14              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.50</b> |
| 30                | 2240        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.