

AS 504

TIRE SIZE	16.0/70 - 20
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	139 A8
LI/SS FREE ROLLING	151 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019045	RC (IN)	126.5
SW (IN)	16.5	RIM REC	13
OD (IN)	43.2	RIM ALT	12 SDC; 14; 13 SDC
SLR (IN)	19.2	ECE	E11-106R-004610

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44
5 FR	10650
15 FR	9050
20 FR	8520
25 FR	7610
5 DW	7500
15 DW	6370
20 DW	6000
25 DW	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.