DATA SHEET

PRINTED ON
23-04-2026

AGRIMAX ELOS

TYRE SIZE	**480/80 R 42**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	151 A8/B

DIMENSIONS US STANDARD

USA CODE	94040827	**RC (IN)**	221.6
SW (IN)	19.3	**RIM REC**	DW 16 L
OD (IN)	74.4	**RIM ALT**	DD 16 L; W 16 L
SLR (IN)	33.7	**ECE**	E4-106R-001481

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
30	4190	4870	5560	6240	6920	7600
25	4190	4870	5560	6240	6920	7600
20	4490	5210	5950	6680	7420	8150
5 LT	5610	6530	7450	8370	9280	10200
5 HT	4490	5210	5950	6680	7420	8150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..