

AGRIMAX RT 855

TIRE SIZE	420/80 R 46
UM	IS STANDARD
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	151 D ; 162 A2



DIMENSIONS IS STANDARD

SW (MM)	418	RIM ALT	W 12
OD (MM)	1840	ECE	E4-106R-001730
SLR (MM)	863	SRI	900
RC (MM)	5641	TRA CODE	R1W
RIM REC	W 13	TREAD DEPTH (MM)	50,5

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1625	1865	2140	2415	2695	2970	3210	3450
50	1705	1960	2250	2540	2830	3120	3375	3625
40	1780	2045	2345	2650	2950	3255	3520	3780
30	1870	2145	2465	2780	3100	3415	3695	3970
10	2235	2565	2945	3325	3705	4085	4420	4750
10 LT	2175	2500	2870	3240	3610	3980	4305	4625
10 HT	1870	2145	2465	2780	3100	3415	3695	3970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.