

# AW 909

<b>TIRE SIZE</b>	11.5/80 - 15.3
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	139 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	300	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	844	<b>ECE</b>	E4-106R-001897
<b>SLR (MM)</b>	370	<b>PR</b>	14
<b>RC (MM)</b>	2473		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.75
10 FR	3400
25 FR	2890
30 FR	2720
40 FR	2430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.