

# MULTIMAX MP 527

<b>TIRE SIZE</b>	<b>460/70 R 24 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	159 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	465	<b>RIM REC</b>	DW 15 L
<b>OD (MM)</b>	1254	<b>RIM ALT</b>	DW 14 L ; DW 16 L
<b>SLR (MM)</b>	574	<b>ECE</b>	E11-106R-002983
<b>RC (MM)</b>	3801	<b>SRI</b>	600

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2100	2495	2845	3240	3635	3895	4375	-	-
40	2100	2495	2845	3240	3635	3895	4375	-	-
30	2250	2675	3050	3470	3890	4170	4685	-	-
25	2335	2775	3160	3600	4035	4330	4860	-	-
10 CYC.	2565	3155	3710	4270	4860	5285	5975	6305	6565
STATIC	3930	4835	5690	6545	7450	8105	9160	9665	10065

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.