


# TR 135

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>13.6 - 38</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTOR / TRAILER  |
| <b>VERSION</b>      | HD   |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 127 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94027156 | <b>RC (IN)</b> | 190.2           |
| <b>SW (IN)</b>  | 13.6     | <b>RIM REC</b> | W 12            |
| <b>OD (IN)</b>  | 61.6     | <b>RIM ALT</b> | W 11            |
| <b>SLR (IN)</b> | 28.9     | <b>ECE</b>     | E11-106R-004455 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>30</b> |
| 25               | 3860      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.