


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>460/65 R 24 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 D ; 156 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	455	<b>RIM REC</b>	DW 14 L
<b>OD (MM)</b>	1214	<b>RIM ALT</b>	DW 15 L ; DW 13
<b>SLR (MM)</b>	549	<b>ECE</b>	E11-106R-005109
<b>RC (MM)</b>	3644	<b>SRI</b>	600

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	1380	1690	1900	2245	2555	2865	3140	3450
50	1490	1830	2050	2425	2760	3095	3395	3730
40	1600	1960	2200	2600	2960	3320	3640	4000
30	1655	2030	2275	3790	3065	3435	3765	4140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.