

AGRIMAX V-FLECTO



TYRE SIZE	VF 480/70 R 34 NRO
UM	IS STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	166 D

DIMENSIONS IS STANDARD

SW (MM)	495	RIM REC	W 18 L
OD (MM)	1580	RIM ALT	W 16 L ; DW 18 L
SLR (MM)	708	ECE	E11-106R-0010578
RC (MM)	4739	SRI	750

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8	3.2
70	1880	2220	2555	2845	3185	3475	3810	4100	4485	4820
FROM 65 TO 40	2070	2440	2810	3130	3500	3820	4190	4505	4930	5300
30	2110	2490	2865	3190	3570	3895	4270	4595	5030	5405
20	2150	2535	2925	3255	3640	3970	4355	4685	5125	5510
10	2275	2685	3090	3440	3850	4200	4610	4960	5425	5830
*UPTO 10 CYC WITH FRONT LOADER	2895	3415	3935	4380	4900	5345	5865	6310	6905	7420
10HT	2110	2490	2865	3190	3570	3895	4270	4595	5030	5405

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.