


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>320/65 R 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINDIMADORA / TRATOR / CEIFEIRA
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	125 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	310	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	885	<b>RIM ALT</b>	W 9 ; W 11
<b>SLR (MM)</b>	400	<b>ECE</b>	E11-106R-008145
<b>RC (MM)</b>	2667	<b>SRI</b>	425

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.8	3.2
<b>50</b>	545	645	745	825	925	1010	1205	1340	1505	1650
<b>40</b>	545	645	745	825	925	1010	1205	1340	1505	1650
<b>30</b>	585	695	800	885	995	1080	1295	1435	1615	1770
<b>10 LT</b>	735	865	1000	1110	1245	1355	1620	1795	2020	2215
<b>10 HT</b>	585	695	800	885	995	1080	1295	1435	1615	1770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.