


# EARTHMAX SR 22 AS

<b>TYRE SIZE</b>	<b>20.5 R 25</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	LOADER
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TL/TT</b>	TL
<b>LI/SS</b>	177 B ; 161 A8 ; 193 A2



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94073160	<b>RIM REC</b>	17.00/2.0
<b>OD (IN)</b>	58.8	<b>TRA CODE</b>	E2/G2/L2
<b>SLR (IN)</b>	25.2	<b>STAR RATING</b>	★★/★/★★
<b>RC (IN)</b>	170.2		

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91
30	-	-	-	-	-	-	-	-	12800	13600	14300	14800	15200	16100	-	-	-	-
25	5360	6150	6950	7600	8550	9100	9650	10200	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	21500	22000	22700	24000	24700
<b>MPH / PSI</b>	<b>94</b>																	
30	-																	
25	-																	
5	25400																	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.