


AGRIMAX V- FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 900/60 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR DE ALTA POTENCIA / TRACTOR |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 189 D |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 900 | RIM REC | DW 30B |
| OD (MM) | 2142 | ECE | E11-106R-006165 |
| SLR (MM) | 937 | SRI | 1025 |
| RC (MM) | 6390 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 |
|--------------------------------|------|------|------|-------|-------|-------|-------|
| 70 | 4590 | 5340 | 6180 | 6930 | 7680 | 8435 | 9370 |
| FROM 65 TO 40 | 5045 | 5870 | 6795 | 7620 | 8445 | 9270 | 10300 |
| 30 | 5145 | 5985 | 6930 | 7770 | 8610 | 9455 | 10505 |
| 20 | 5245 | 6100 | 7065 | 7920 | 8780 | 9640 | 10710 |
| 10 | 5545 | 6455 | 7470 | 8380 | 9285 | 10195 | 11330 |
| *UPTO 10 CYC WITH FRONT LOADER | 7060 | 8215 | 9510 | 10665 | 11820 | 12975 | 14420 |
| 10 HT | 5145 | 5985 | 6930 | 7770 | 8610 | 9455 | 10505 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.