


MULTIMAX MP 515

| | |
|---------------------|------------------------------------------------------------------------------------------|
| TIRE SIZE | 445/65 R 22.5 MPT |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VEHICUL UNIVERSAL / CAMION PENTRU ÎNGRĂȘĂMINTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 160 G |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94057207 | RC (IN) | 139.1 |
| SW (IN) | 17.5 | RIM REC | 13 |
| OD (IN) | 45.3 | RIM ALT | 14 |
| SLR (IN) | 20.7 | ECE | E11-54R-0017868 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 36 | 44 | 51 | 58 | 65 | 87 |
|-----------|------|------|------|------|------|------|------|-------|
| 55 | 3840 | 4540 | 5310 | 6060 | 6780 | 7470 | 8380 | 9920 |
| 40 | 4170 | 4930 | 5760 | 6580 | 7360 | 8100 | 8820 | 10770 |
| 25 | 4420 | 5210 | 6110 | 6980 | 7800 | 8600 | 9350 | 11410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.